Bull Creek Tech

960GB M.2 2230 PCIe Gen4 x4 SSD NDAA Single Sided/ TAA & NDAA Compliant

SKU: 960G2230SSNDAA

UPC: 810189122499



- 960GB capacity in a M.2 2230 (22 x 30 mm) form factor - drop-in upgrade for handheld gaming PCs, slim 2-in-1s, and ultrabooks
- PCIe Gen 4 x4 NVMe interface delivers up to 5,000 MB/s read / 4,500 MB/s write for fast boot, application loads, and large file transfers
- iTemp screened for a 0°C to 85°C operating temperature range - qualified for industrial, embedded, and field-deployed systems
- TAA-compliant, manufactured in Mexico - qualifies for federal, state, and education procurement
- NDAA-compliant build - Section 889 documentation scoped to your solicitation available on request
- Validated against major OEM systems for OEM-grade compatibility
- 3-year limited warranty with US-based support and rapid RMA
- Single-sided PCB design fits thin chassis where double-sided drives won't clear (handheld gaming PCs, slim notebooks, blade workstations)

Built for Business

960GB TAA-compliant M.2 2230 solid state drive (22 x 30 mm) for compact handheld and ultraportable systems. PCIe Gen 4 x4 NVMe interface delivers up to 5,000 MB/s read / 4,500 MB/s write. iTemp screened for a 0°C to 85°C operating temperature range. 3-year warranty. Tested for compatibility with major OEM platforms. NDAA-compliant configuration with Section 889 documentation available for federal and regulated procurements.

Technical Specifications

Product Type	Solid State Drive
Storage Capacity	960 GB
Drive Type	Internal
Drive Interface	PCI Express NVMe
Drive Interface Standard	PCI Express NVMe 4.0 x4
Form Factor	M.2 2230
PCB Configuration	Single-Sided
Dimensions (W x L x H)	0.9" x 1.2"
Operating Temperature	0°C to 85°C (iTemp Screened)
Device Supported	Desktop PC, Notebook, Motherboard

Bull Creek Tech

Country of Origin	Mexico
TAA Compliant	Yes
NDAA Compliant	Yes
Limited Warranty	3 Year

Warranty

3-Year Limited Warranty

Environmental

Non-Operating Temperature	-40°C to 85°C
Operating Humidity	5% to 95% relative
Shock	1500G / 0.5ms
Vibration	2-500Hz, 3.1G

Part Number

960G2230SSNDAA