Bull Creek Tech

2TB M.2 2230 PCIe Gen4 x4 SSD NDAA Single Sided/ TAA & NDAA Compliant

SKU: 2T2230SSNDAA

UPC: 810189122529



- 2TB capacity in a M.2 2230 (22 x 30 mm) form factor - drop-in upgrade for handheld gaming PCs, slim 2-in-1s, and ultrabooks
- PCIe Gen 4 x4 NVMe interface delivers up to 5,000 MB/s read / 4,500 MB/s write for fast boot, application loads, and large file transfers
- iTemp screened for a 0°C to 85°C operating temperature range - qualified for industrial, embedded, and field-deployed systems
- TAA-compliant, manufactured in Mexico - qualifies for federal, state, and education procurement
- NDAA-compliant build - Section 889 documentation scoped to your solicitation available on request
- Validated against major OEM systems for OEM-grade compatibility
- 3-year limited warranty with US-based support and rapid RMA
- Single-sided PCB design fits thin chassis where double-sided drives won't clear (handheld gaming PCs, slim notebooks, blade workstations)

Built for Business

2TB TAA-compliant M.2 2230 solid state drive (22 x 30 mm) for compact handheld and ultraportable systems. PCIe Gen 4 x4 NVMe interface delivers up to 5,000 MB/s read / 4,500 MB/s write. iTemp screened for a 0°C to 85°C operating temperature range. 3-year warranty. Tested for compatibility with major OEM platforms. NDAA-compliant configuration with Section 889 documentation available for federal and regulated procurements.

Technical Specifications

Product Type	Solid State Drive
Storage Capacity	2 TB
Drive Type	Internal
Drive Interface	PCI Express NVMe
Drive Interface Standard	PCI Express NVMe 4.0 x4
Form Factor	M.2 2230
PCB Configuration	Single-Sided
Dimensions (W x L x H)	0.9" x 1.2"
Operating Temperature	0°C to 85°C (iTemp Screened)
Device Supported	Desktop PC, Notebook, Motherboard

Bull Creek Tech

Country of Origin	Mexico
TAA Compliant	Yes
NDAA Compliant	Yes
Limited Warranty	3 Year

Warranty

3-Year Limited Warranty

Environmental

Non-Operating Temperature	-40°C to 85°C
Operating Humidity	5% to 95% relative
Shock	1500G / 0.5ms
Vibration	2-500Hz, 3.1G

Part Number

2T2230SSNDAA